OPTICON

Data Collectors

OPL9727

Barcode laser scanner

IrDA

Serial cradle

Modem cradle

GSM cradle

+ Related products

OPL9724
- Data Collector
- Barcode laser scanner
- IrDA, Bluetooth
- 3 key operation

OPL9728
- Data Collector
- Barcode laser scanner
- IrDA

OPN2001
- Data Collector
- Pocket memory scanner
- USB

+ Basic Product Specifications

Operation
- CPU: 16-bit
- O/S: Proprietary
- Software: Programmable in C-language. Ansi-C Cross compiler obtainable. Software development kit free downloadable
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory
- FlashROM: 512 kB
- RAM: 128 kB

Operating indicators
- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Operating keys
- Entry options: 3 keys total,
  2 function keys,
  1 scan key

Communication
- IrDA: Ver. 1.2, baudrate 2400 bps - 115.2 kbps

Power
- Rechargeable battery: Lithium-Ion 3.7V 600mAh
- Backup battery: Lithium rechargeable 3.5mAh
- Operating time: Ca. 200 hours (1 scan / 5 sec with 1 sec laserbeam on, 0.2 sec green LED on, 0.2 sec buzzer on)
- Data retention time: Ca. 72 hours
- Charging method: Separate cradle CRD9720 series

Barcode scanner Optics
- Light source: 650 nm visible laser diode
- Scan method: Vibrating mirror
- Scan rate: 100 scans/sec
- Reading pitch angle: -25 to 0º, 0 to +25º
- Reading skew angle: -50 to -8º, +8 to +50º
- Reading tilt angle: -20 to 0º, 0 to +20º
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9, Code 39
  60 - 300 mm / 2.36 - 11.81 in (1.0 mm / 39 mil),
  35 - 210 mm / 1.38 - 8.27 in (0.5 mm / 20 mil),
  35 - 120 mm / 1.38 - 4.72 in (0.25 mm / 10 mil),
  35 - 70 mm / 1.38 - 2.76 in (0.15 mm / 6 mil)

Supported Symbologies
- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/ NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN, Matrix 2of5, MSI/ Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite Codes, MicroPDF417, PDF417

Durability
- Temperature in operation: -5 to 40 ºC / 23 to 104 ºF
- Temperature in storage: -20 to 60 ºC / -4 to 140 ºF
- Humidity in operation: 20 - 80% (non-condensing)
- Humidity in storage: 20 - 90% (non-condensing)
- Ambient light immunity: White 3,000 lx max, Fluorescent 3,000 lx max, Direct sun 50,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 12 - 100 Hz with 2G for 1 hour
- Protection rate: IP 54

Physical
- Dimensions (w x h x d):
  44 x 125 x 19 mm / 1.73 x 4.92 x 0.75 in
- Weight body: Ca. 85 g / 3 oz (incl. battery)
- Case: ABS, Lilacgrey

Regulatory & Safety
- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 1, IEC 60825-1 Class 1, FDA CDRH Class I

Enclosed items
- Rechargeable battery
- Hand strap

Sold separately
- CRD9722 Cradle: Charging
- CRD9723RU Cradle: Serial communication, charging
- CRD9723RU1 Cradle: Multi-cradle, 1x communication, 5x charging
- CRD9723RU5 Cradle: Multi-cradle, 5x communication, 5x charging
- CRD9726 Cradle: Modem communication, charging
- CRD9727 Cradle: GSM communication, charging
- OPL9700 Nylon case with swivel clip & window
- OPL9700 Nylon case with swivel clip
- OPL9700 Nylon case with fixed clip

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON

WWW.OPTICON.COM

Solutions for Automatic Identification, Barcodes and Mobility

More than 3000 customers in 15 countries • More than 12,000 products in stock

www.logiscenter.com
902 050 030

www.logiscenter.it
02 479 216 97

www.logiscenter.de
info@logiscenter.de

www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the befenits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permament stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands

MOTOROLA
ZEBRA TECHNOLOGIES
Intermec
Honeywell
DATALOGIC
datamax·o'neil
Metrologic
LXE
EPSON
elo
star
unitech
PRINTRONIX
symbol

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health

Label printers

Barcode readers

Data terminals & PDA

PVC card printers



RFID

Consumables
(labels, ribbons, PVC cards)

All Brands Technical Service

GRUPO LOGISCENTER, S.L. - The Barcode Solutions Center
Av. Puente Cultural 10-A • 28702 San Sebastián de los Reyes - MADRID (Spain)
CIF ES B85538601 • info@logiscenter.com • www.logiscenter.com