



# FARGO® DTC1250e

**The DTC1250e offers the following built-in and optional features:**

- A dual-sided printing module that enables you to add additional company or cardholder information as needed.
- A Wi-Fi accessory for Ethernet-enabled printers, allowing you to print anywhere, anytime.
- Choose from either the easy-to-use all-in-one ribbon cassette (EZ ribbons) or the more economical and eco-friendly refill ribbon (ECO ribbons) option.
- An optional iCLASS SE® encoder that enables your printer to be compatible with the HID secure identity ecosystem. This includes the ability to program the HID PACS data in the printer. The encoder provides an additional layer of security to your identity program by allowing for processing of Secure Identity Object (SIO) data, and enabling the printer to become a Trusted Identity Platform (TIP) endpoint.
- Optional internal server for secure printing over a network, enabling distributed card issuance in seconds.
- Optional technology card encoders that allow you to easily migrate to contact and contactless smart card technologies (including but not limited to iCLASS SE® or MIFARE™) or simple mag stripe and prox cards as needed.
- Eco-friendly erase and rewrite feature, ideal for creating temporary ID cards, such as visitor badges.
- Ability to print on a variety of card thicknesses to create simple loyalty cards as thin as 9 mil, or access control badges as thick as 40 mil.

## DIRECT-TO-CARD PRINTER

- **Fastest printer in its class** - Minimize wait time for cards and IDs with this speedy card printer.
- **High-quality output** - Simple, reliable and affordable photo ID card personalization, delivering a new level of durable, great-looking credentials.
- **Simple plug-and-play** - The intuitive user-focused design allows for easy set-up, loading and operation for increased efficiency.
- **Convenient and affordable** - Create ID cards right out of the box with plug-and-play Swift ID™ embedded badging application.
- **End-to-End Control, Flexibility and Security** - The optional iCLASS SE® encoder (part of the iCLASS SE open encoder platform) can be fully integrated into your printer, allowing you to create, encode (read/write) and manage your secure credentials from start-to-finish. Design personalized ID badges locally and then program them to work with your current physical access control system (PACS), streamlining your ordering, inventory management, and issuance processes.
- **Additional Data Protection** - Secure data sent to printer with AES-256 decryption.

Designed for small-to-medium businesses, the DTC1250e provides maximum efficiency in a sleek, user-friendly design. This printer is virtually maintenance-free and prints full-color, plastic ID and technology cards on a budget.

**The DTC1250e adds a level of convenience to easily print what you need, including:**

- Choose from easy (EZ), all-in-one print ribbon and card cleaner or economical and eco-friendly (ECO) refill ribbons.
- Built-in Swift ID™ badging application enables you to create ID badges in seconds without having to install any additional software.

- Edge-to-edge printing in full-color or simple black and white.
- Intuitive design provides instant system status through color-changing buttons.
- Industry's first, inline card printing and technology card encoding with a single connection using USB or optional Ethernet or Wi-Fi connectivity.

The FARGO® DTC1250e is built with Genuine HID® technology and is fully interoperable with other products in the HID ecosystem, enabling organizations to leverage their existing technology investments.



## SPECIFICATIONS

<b>Print Method</b>	Dye-sublimation / resin thermal transfer
<b>Resolution</b>	300 dpi (11.8 dots/mm) continuous tone
<b>Colors</b>	Up to 16.7 million / 256 shades per pixel
<b>Print Ribbon Options</b>	<p><b>Options include easy-to-use ribbon with disposable ribbon cartridge (EZ) and more economical and ecofriendly refill ribbon for cartridge (ECO).</b></p> <p><b>Both EZ and ECO:</b></p> <ul style="list-style-type: none"> <li>Full-color with resin black and overlay panel, YMCKO*, 250 prints</li> <li>Resin black (standard), 1000 prints</li> </ul> <p><b>ECO only:</b></p> <ul style="list-style-type: none"> <li>Full-color half-panel with resin black and overlay panel, YMCKO*, 350 prints</li> </ul> <p><b>EZ only:</b></p> <ul style="list-style-type: none"> <li>Full-color with two resin black panels and overlay panel, YMCKOK*, 200 prints</li> <li>Resin black and overlay panel, KO*, 500 prints</li> <li>Resin black (premium), 1000 prints</li> <li>Dye-sublimation black and overlay panel, BO*, 500 prints</li> <li>Resin green, blue, red, white, silver, gold, 1000 prints</li> <li>Silver and gold metallic, 500 prints</li> </ul> <p>Rewrite technology - no ribbon is required</p>
<b>Print Speed**</b>	6 seconds per card (K*); 8 seconds per card (KO*); 16 seconds per card (YMCKO*); 24 seconds per card (YMCKOK*)
<b>Accepted Standard Card Sizes</b>	CR-80 (3.375"L x 2.125" W / 85.6 mm L x 54 mm W); CR-79 adhesive back (3.313"L x 2.063" W / 84.1 mm L x 52.4 mm W)
<b>Print Area</b>	CR-80 edge-to-edge (3.36"L x 2.11" W / 85.3 mm L x 53.7 mm W); CR-79 (3.3"L x 2.04" W / 83.8 mm L x 51.8 mm W)
<b>Accepted Card Thickness</b>	.009" - .040" / 9 mil - 40 mil / .229 mm - 1.016 mm
<b>Accepted Card Types</b>	PVC or polyester cards with polished PVC finish; monochrome resin required for 100% polyester cards; optical memory cards with PVC finish; rewrite
<b>Input Hopper Card Capacity</b>	100 cards (.030" / .762 mm)
<b>Output Hopper Card Capacity</b>	Single Sided: Up to 30 cards. Dual Sided: Up to 100 cards. (.030" / .762 mm)
<b>Card Cleaning</b>	Card cleaning roller integrated into ribbon cartridge; cleaning roller is automatically replaced with each ribbon change
<b>Memory</b>	32 MB RAM
<b>Software Drivers</b>	Windows XP / Vista™ (32 bit & 64 bit) / Server 2003 & 2008 / Windows 7 / Windows 8 (32 bit & 64 bit) / MAC OS X 10.5/10.6/10.7/10.8/10.9 / Linux*** (Available Soon)
<b>Interface</b>	USB 2.0, optional Ethernet with internal print server
<b>Operating Temperature</b>	65° to 80° F / 18° to 27° C
<b>Humidity</b>	20-80% non-condensing
<b>Dimensions</b>	Single-sided printer: 8.8"H x 13.7"W x 7.9"D / 224 mm H x 348 mm W x 201 mm D Dual-sided printer: 9.8"H x 18.7"W x 9.2"D / 249 mm H x 475 mm W x 234 mm D
<b>Weight</b>	Single-sided: 7.5 lbs / 3.4 Kg; dual-sided: 10 lbs / 4.54 Kg
<b>Agency Listings</b>	Safety: UL 60950-2, CSA C22.2 (60950-07), and CE; EMC: FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, BSMI, KC
<b>Environmental Features</b>	ENERGY STAR® qualified card printer (base models only without encoders) and refillable supply cartridges (ECO)
<b>Supply Voltage</b>	100-240Vac, 50-60Hz, 1.6 Amps max
<b>Supply Frequency</b>	50 Hz / 60 Hz
<b>Warranty</b>	Printer - three years; printhead - three years, unlimited pass with UltraCard®
<b>Encoding Options</b>	Supported smart card and magnetic stripe technologies: 125 kHz (HID Prox) reader; 13.56 MHz (iCLASS® Standard / SE / SR / Seos, MIFARE Classic®, MIFARE Plus®, MIFARE DESFire®, MIFARE DESFire® EV1, ISO 14443 A/B, ISO 15693) read/write encoder; contact smart card encoder reads from and writes to all ISO7816 1/2/3/4 memory and microprocessor smart cards (T=0, T=1) as well as synchronous cards; ISO magnetic stripe encoding, dual high- and low-coercivity, tracks 1, 2 and 3
<b>Supported Access Control Credential Programming</b>	iCLASS® Standard/SE/SR/Seos, MIFARE Classic™, MIFARE DESFire® EV1, HID Prox
<b>Options</b>	Single wire Ethernet and USB 2.0 interface for inline printing and encoding (note: single wire Ethernet encoding is only available for iCLASS®, MIFARE®, and contact smart card encoding) - Ethernet-enabled printer supports wireless accessory; dual-sided printing module; smart card encoding modules (contact/contactless); magnetic stripe encoding module; printer cleaning kit; ethernet with internal print server; secure proprietary consumables system
<b>Software</b>	Swift ID™ embedded badging application, FARGO Workbench™ diagnostic utility with Color Assist™ spot-color matching
<b>Display</b>	Color changing status buttons

\* Indicates the ribbon type and the number of ribbon panels printed where Y=yellow, M=magenta, C=cyan, K=resin black, O=overlay, B=dye sublimation black.

\*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.

\*\*\*Linux versions: Ubuntu 12.04, Debian 7.0, Fedora 18, Mandriva 2011, Red Hat 6.4, Open Suse 12.3



hidglobal.com

North America: +1 512 776 9000

Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800

Latin America: +52 55 5081 1650



Learn about HID Global's green initiative @  
hidglobal.com/green

© 2015 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and Ultracard, Swift ID, SmartScreen, MIFARE Plus, MIFARE DESFire, iCLASS and FARGO are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
2015-02-18-fargo-dtc1250e-printer-ds-en PLT-01776

An ASSA ABLOY Group brand

ASSA ABLOY



800 729 0236  
www.logiscenter.us



0241 9550 9225  
www.logiscenter.de



01 82 88 44 70  
www.logiscenter.fr



020 3318 8265  
www.logiscenter.co.uk



0720 115814  
www.logiscenter.at



02 58 80 583  
www.logiscenter.be



911 433 048  
www.logiscenter.com



02 4792 1697  
www.logiscenter.it



308 800 842  
www.logiscenter.pt

## About LOGISCENTER

Logiscenter is the leading provider of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 60,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products, we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.



## All Brands Technical Service


## Our Brands



## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)